Жидкость трансмиссионная 8HP Fluid для гидротрансформаторных автоматических коробок передач

Полностью синтетическая трансмиссионная жидкость на основе гидрокрекингового базового масла и ПАО с добавлением специального комплекса присадок и ингибиторов, обеспечивающих бесперебойную работу АКПП.



Область применения: рекомендации по использованию: предназначено для современных 8-ми ступенчатых АКПП ZF всех типов серии HP 8HP45, 8HP55, 6HP26, 8HP70, 8HP90, а также и для 6-ступенчатых АКПП серии HP 6HP19X для AUDI Q7, 6HP19A, 6HP28AF. Также может применяться для АКПП ZF серии 9HP48. Не подходит для вариаторов (CVT) и роботизированных коробок передач с двумя сцеплениями (DCT/DSG).

Соответствует требованиям: BMW 83222152426 ATF L 12108/83222289720/83222305397 (до 02.2013 83222152426); Fiat 9.55550-AV5; Honda/Acura 08200-9016A/ATF Type 3.0; HONDA 08200-9017/ATF Type 3.1; Land Rover LR023288/LR023289; MOPAR 68157995AB/68218925AA ;VW/AUDI G 060162 A1/G 060162 A2/G 060162 A6; VW G055162; ZF S671 090 312/TE-ML 11 9HP48

Фасовка и артикул:
1 литр - 8HP-001-108
5 литров - 8HP-005-108

Наименование показателя	Ед. изм.	Метод испытаний	Результаты испытаний
Индекс вязкости	ед.	ASTM D 2270	171
Плотность при 15 °С	г/см^3	ASTM D 4052	0,9
Кинематическая вязкость при 100°С	сСт	ASTM D 445	6,7
Кинематическая вязкость при 40°С	сСт	ASTM D 445	32,3
Общее кислотное число	мг КОН/г	ASTM D 664	0,2
Температура вспышки в открытом тигле	°С	ASTM D 92	195
Температура застывания	°С	ГОСТ 20287-91 (метод Б)	-45

Эти характеристики являются типичными для текущего производства. Данные не являются гарантией наличия определенных свойств или пригодности для конкретной области применения. Ответственность за соблюдение действующих положений законодательства и нормативных документов, регламентирующих использование продукции, возлагается на получателя наших продуктов. Компания ZEFFO постоянно совершенствует свою продукцию. Поэтому компания ZEFFO сохраняет за собой право в любое время и без предварительного уведомления вносить изменения в технические характеристики, приведенные в данной информации о продукте.

info@zeffo.ru
8 800 707 96 05
www.zeffo.ru

Transmission Fluid 8HP Fluid for Torque Converter Automatic Transmissions



Fully synthetic transmission fluid based on hydrocracked base oil and PAO with the addition of a special additive package and inhibitors that ensure uninterrupted operation of the automatic transmission.

Application: Recommended use: intended for modern 8-speed ZF automatic transmissions of all types in the HP series 8HP45, 8HP55, 6HP26, 8HP70, 8HP90, as well as for 6-speed automatic transmissions of the HP series 6HP19X for AUDI Q7, 6HP19A, 6HP28AF. It can also be used for ZF automatic transmissions of the 9HP48 series. Not suitable for CVTs (continuously variable transmissions) and dual-clutch robotic transmissions (DCT/DSG).

Meets requirements: BMW 83222152426 ATF L 12108/83222289720/83222305397 (до 02.2013 83222152426); Fiat 9.55550-AV5; Honda/Acura 08200-9016A/ATF Type 3.0; HONDA 08200-9017/ATF Type 3.1; Land Rover LR023288/LR023289; MOPAR 68157995AB/68218925AA ;VW/AUDI G 060162 A1/G 060162 A2/G 060162 A6; VW G055162; ZF S671 090 312/TE-ML 11 9HP48

Packaging and article number:
1 liter - 8HP-001-108
5 liters - 8HP-005-108

Parameter	Unit	Test Method	Test Results
Viscosity Index	units	ASTM D 2270	171
Density at 15ºC	g/cm³	ASTM D 4052	0.9
Kinematic Viscosity at 100ºC	cSt	ASTM D 445	6.7
Kinematic Viscosity at 40ºC	cSt	ASTM D 445	32.3
Total Acid Number	mg KOH/g	ASTM D 664	0.2
Flash Point (open cup)	ºC	ASTM D 92	195
Pour Point	ºC	GOST 20287-91 (Method B)	-45

These characteristics are typical of current production. The data do not guarantee the presence of specific properties or suitability for a particular application. Responsibility for compliance with applicable legal provisions and regulatory documents governing the use of the products rests with the recipient of our products. ZEFFO continuously improves its products. Therefore, ZEFFO reserves the right to make changes to the technical specifications provided in this product information at any time and without prior notice.

info@zeffo.ru
8 800 707 96 05
www.zeffo.ru